

**Material:**

Anschlüsse: Kupferlegierung, verzinkt

Verpackungsmöglichkeiten:

2.000 St./ Rolle

Materials:

Clip Terminals: Tin Plated Inconel Alloy

Packing options:

2.000 pcs. / reel

Technische Spezifikation /**Technical Spezification:****Schock /Schock Resistance:**

MIL-STD-202G, Method 213 B, Test Condition I

Vibration /Vibration Resistance:

MIL – STD-202G, Method 201

Isolationswiderstand /Insulation Resestance:

MIL-STD-202G, Method 302

Test Condition A 10.000 ohms min.

Lötbarkeit /Solderability:

MIL-STD-202G, Method 208

Temperaturtest / Thermal Shock:

MIL-STD-202, Method 107, Test Condition B

Temperaturbereich / Operating Temperature:

-55 °C to 125 °C

Bemessungswerte / Ratings

SSQ Keramikkörper flink SSQ Square Ceramic Surface Mount Quick Action Fuse	
Bestellnummer	Strom / Current
SSQC 250	250 mA
SSQC 375	375 mA
SSQC 500	500 mA
SSQC 750	750 mA
SSQC 1	1 A
SSQC 1,25	1,25 A
SSQC 1,5	1,5 A
SSQC 2	2 A
SSQC 2,5	2,5 A
SSQC 3	3 A
SSQC 3,5	3,5 A
SSQC 4	4 A
SSQC 5	5 A
SSQC 6,3	6,3 A
SSQC 7	7 A
SSQC 8	8 A

